

logiJET TC6

Ideal for:

- Hazard Warning Chemical Container Labels
- GHS-compliant hazardous materials labeling
- Price labeling
- Logistics
- Medical and Pharmaceuticals
- Department of Transportation
- Food Industry (Including Farm-to-Table)

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Twin-Engine, 6", Two-Color, Thermal Transfer Printer
- Perfect Solution for New GHS Requirements!
- BS5609 Certified TT Ribbons and Labels are Available
- "Ribbon Saver" Feature on Second Print Engine!
- For Label Rolls up to a Diameter of 12" (300 mm)
- Rewinders with Independent Power Supply Available
- Industrial Grade Engine, with Compact Cover
- 2 USB Slots for Connection of USB Keyboard / USB Sticks
- Compact Flash Card Slot

**MEETS NEW GHS COMPLIANT
AND BS5609 CERTIFIED,
LABEL STANDARDS**

logiJET TC6



The logiJet TC6 is a twin-engine 6" wide, Thermal Transfer Printer capable of printing two-color labels simultaneously. Perfect for on demand variable data or batch label printing, the logiJet TC6 Thermal Transfer Printer can produce fully qualified GHS and BS5609 compliant two-color Chemical Labels when matched with certified TT Ribbons and Labels.

Print Engine

Print technology	2 Head Thermal Transfer Printing
Controller	High Speed 32 Bit
Print speed	up to 4.72 inch/s up to 120 mm/s
Print resolution	Near Edge 305 dpi
Power consumption	1.5-3 A 110 -230 V/50 – 60 Hz
Dimensions (WxDxH in mm)	13" x 19" x 15" (335 x 475 x 380 mm) 13" x 33" x 16" (335 x 825 x 410 mm) Incl. External Unwinder
Weight	59.5 lb. (approx. 22 kg) 65.7 lb. with External Unwinder
Environment temperature	41 – 95 °F, 5 – 35 °C
Relative humidity	max 80% (non-condensing)
Interfaces	Serial: RS-232C (max 115,200 Baud) Parallel: Centronics (SPP) USB: 2.0 High Speed Slave LAN: 10/100 Base T, LPD, RawIP-Printing, DHCP, HTTP, and FTP, 2 x USB Master: connection for external USB keyboard and memory stick
Memory	16 MB / 64 MB (on demand)

Barcodes and Features

Barcodes

1D Bar Codes: CODABAR, Code 128, Code 2/5 interleaved, Code 39, Code 39 extended, Code 93, EAN 13, EAN 8, EAN ADD ON, GS1-128, Identcode, ITF 14, Leitcode, Pharmacode, PZN 8 Code, UPC-A, UPC-E

2D Bar Codes: Aztec Code, CODABLOCK F, DataMatrix, GS1 DataMatrix, MAXICODE, PDF 417, QR Code

GS1 Bar Codes: GS1 DataBar Expanded, GS1 DataBar Limited, GS1 DataBar Omnidirectional, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Truncated

Fonts

6 bitmap fonts, 8 vector fonts/TrueType fonts, 6 proportional fonts, more fonts on demand

Additional functions

Tear-off edge
Real time clock with printout date and time
Automatic daylight saving time
Storage of print files in the printer
USB host for connection of an external USB keyboard and an USB memory stick
Ethernet interface
Label photocell
(transmission and reflexion from below)
Compact Flash card slot
Windows printer driver



Printable Media

Size

Media Width 50 - 176 mm
width printable
width max.
160 mm

Media Length 25 - 800 mm
length

Paper thickness max 220 g/m²

Media Core diameter 40 mm / 75 mm (option)

Media Roll diameter 300 mm

Thermal Ribbon

Thermal transfer

ribbon roll diameter max. 90 mm

Ribbon length max. 450 m

Coated side outside or inside

Ribbon width max. 163 mm

Paper Path

Input

continuous external from roll

external, e.g. fanfold

sensor for black mark and label gap (reflection and transmissive)

Output

Single / Job tear-off

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 7.1 - 11.05.2015

