

PP 806 The Multifunctional, High Speed, Impact Printer



PP 806 with optional Printer Stand, 3 ASF-Cassettes and Cut Sheet tray.

- Heavy duty, 24-wire, Dot Matrix Printer with Intellidrive™ - Technology
- Flat bed technology using print bar
- Robust design for Industrial Applications
- High print performance:
700 chars/sec (10 cpi)
580 pages/hour
40,000 pages/month
- Up to 7 excellent copies (1+6)
- Up to 6 paper inputs,
Up to 3 paper outputs
- Low cost per page using
30 million character ribbon
- Printing width up to
165 columns (10 cpi)
- Easy User operation via
macro functions
- Personality Modules
(interfaces) for major host
and network environments

The **PP 806** is the professional solution for heavy duty, flexible and cost-efficient printing. This multi-purpose Printer can take advantage of up to 6 different paper inputs, for fanfold and cut sheet paper: 2 removable tractor cassettes for fanfold paper, 1 manual front insertion, for cut sheets and 3 optional sheet feeders, for flexibility in printing. Reliable connectivity for any network environment, utilizing the PSi connectivity concept, (PM - Personality Modules), insures the **PP 806** is the right solution for your Impact Printer needs!

IMPORTED by:



PRODUCED by:



TECHNICAL DATA

Printer Specification

Technology:	Serial impact, Dot matrix
Print Head:	24 wires, 0.25 mm (0.01 inch) needle diameter Life time approx. 400 million characters
Print Mode:	High Speed Draft (HSD), Data (DQ), Near Letter Quality (NLQ) and Letter Quality (LQ)
Print format:	Up to 165 characters at 10 characters per inch (cpi)
Ribbon:	Cartridge, nylon Ribbon, Black, 30 million characters, Auto Ribbon run control
Dimensions:	734 x 280 x 295 mm (WxDxH) (28.9 x 11.0 x 11.3 inch)
Weight:	44 pounds (20 kg)
Diagnostics:	Self-test, hex-dump, remote diagnostics via interface
Operator Panel:	16 digit LCD display, tri-lingual (German, English, French)
Keyboard:	Membrane tactile type with Ready/Stop LED
Rated Voltage:	100 - 125 VAC, 200 - 240 VAC max. 3A / 1.5A, 50 - 60 Hz
Power Input:	Operating < 200 W, Standby < 30 W
Environmental Conditions:	Operating: +10°C to +35 °C (+50°F to +95°F) 20% to 80% relative humidity Storage: -40°C to +70 °C (-40°F to +158°F) 5% to 85% relative humidity
Noise Level:	53 dB(A) acceptable to ISO 7779
Agency Approvals:	VDE/GS, UL, C-UL, CE, FCC-B

Performance

Print Speed: (10 cpi)	HSD: 700 cps DQ: 600 cps NLQ: 300 cps LQ: 150 cps
Throughput: (ECMA 132)	DQ: 580 pages/hour LQ: 260 Pages/hour
Duty Cycle:	40,000 pages per month
MTBF:	15,000 hours at 30% duty cycle

Paper Handling

Paper Path:	Fan-fold paper. Paper path selectable via software or Operator Panel.
Automatic Gap Control (AGC):	AGC , automatically optimizes the print head gap based on media thickness.
Copies:	1 original + 6 copies; max. 0.6 mm (0.024 inch) paper thickness, 1 original without copies max. 1.0 mm (0.04 inch) paper thickness, 2.0 mm (0.08 inch) transportation
Paper Input:	Fanfold Paper 2 removable Tractor Cassettes
Paper Output:	Exits at the rear side, with zero-tear-off
Paper Width:	102 to 450 mm (4" to 17.7" inch)
Paper Weight:	60 to 120 g/m ² ; form sets up to 350 g/m ²
Form Feed:	20 inch/second
Paper Input:	Cut Sheets Manual front insertion; up to 3 Optional, Automatic Sheet Feeders
Paper Output:	User selectable at front or rear of Printer
Paper Width:	Manual up to 420 mm (16.6 inch), ASF 4 to 12.2 inch
Paper Weight:	Manual 60 to 170 g/m ² , ASF refers to options

Personality Modules (PM)

	PERSONALITY MODULE (SER/PAR)
Interfaces:	IEEE 1284 and serial RS-232C/RS422, shared mode
Emulations:	IBM Proprinter XL24 (AGM), Epson LQ 2550/1060/ESC/P2, up to 64 KByte
Buffer:	ISO 8859/1, ISO 8859/9, 8859/15; IBM Set 1/Set 2 in 14 national versions; IBM Code Pages 437, 850, 857, 858, 860, 863, 865; Epson Ext. Char. Set in 15 National versions; Eastern European character sets 771, 773, 774, 775, 852, 1125, 1251; Baltic RiM, Greek, CZ, HUN, Russia, Win Lat 2
Character sets:	Draft quality: High Speed Draft, Data and Data Large; Near letter and letter quality: Courier, Sans Serif, OCR-A, OCR-B, Orator, Orator-C, Prestige, Roman, Script, Sans script
Fonts:	Bold, italic, shadow, outline, double strike, underline, double underline, over line, strike through, sub/superscript, double to octuple, for Data Large 99-fold size
Character attributes:	10, 12, 15, 17.1, 18 and 20 cpi, proportional 2, 3, 4, 6, 8, ... 360 lpi
Pitches (cpi):	EAN 8, EAN 13, UPC-A, UPC-E, Postnet, KIX Code, Code 39, Code 93, Code 128 (incl. EAN 128), Codabar, 2 of 5 industrial, 2 of 5 interleaved, and MSI Mod 10/10
Line spacing (lpi):	360 x 360 dpi max.
Barcode:	Parameter settings, up to four individual Printer Configurations, selectable via software or Operator Panel
Graphics:	
Macros:	

Additional, Optional PERSONALITY MODULES

Ethernet:	Ethernet 10BaseT / 100BaseTX RJ45
IPDS:	Ethernet
IGP:	SER/PAR with Printronix IGP 10/20/40 emulation
HP:	SER/PAR or Ethernet with HP2934/2235emulation
GENICOM:	SER/PAR or Ethernet with Genicom 3840 emulation
MT50:	SER/PAR or Ethernet with MT50 emulation
String change:	SER/PAR or Ethernet

(NOTE: Printer Drivers for Windows and SAP R/3 device types, are available for download at <http://www.bsiprinters.com>.)

Options

ASF Cassettes:	Up to 3 automatic Sheet Feeders; paper size: DIN A4, A4 landscape, A5, A6, B5, Letter, Legal Cut sheets form 70 to 100 g/m ² , form sets up to 260 g/m ² ; capacity: 180 sheets, 80 g/m ² paper width up to 305 mm, (12 inch)
Cassette A2:	Media - 100 to 150 g/m ² ; form sets up to 300 g/m ² ; Envelopes from 70 to 90 g/m ² ; Capacity: 40 Envelopes, 70 g/m ²
Cassette B2:	Thick and non-flexible Sheets, Envelopes up to 300 g/m ² . Documents with middle fold
Cassette C:	Front-side stacking of up to 80 sheets, installation in the upper Tractor guide instead of Tractor cassette
Cut Sheet Stacker:	
Printer Stand:	Media handling of dual, fanfold paper input; dimensions: 450 x 660 x 840 mm (W x D x H) (17.7 x 26.4 x 33.6 inch); Weight: approx. 35 pounds (16 kg)
Stacker Option:	Stacks up to 2,000 pages, in use with the Printer Stand

Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

MICROPLEX Printware Corporation

100 Northfield Road
Bedford, OH 44146 USA
Tel: 877-997-6543
Fax: 440-374-2422

info@microplex-usa.com
www.microplex-usa.com



Partners with:

